

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE

|                            | Standard   | Tarkett value                             |
|----------------------------|------------|---|
| <b>Classification</b>      | -          | Rubber Floor Tile (ASTM F1344)            |
| <b>Total thickness</b>     | ASTM F386  | 0.125 " (3.18 mm)                         |
| <b>Installation method</b> | -          | Glue-Down                                 |
| <b>Pattern</b>             | -          | Organics                                  |
| <b>Pattern type</b>        | -          | Allover                                   |
| <b>Format Type</b>         | -          | Tile                                      |
| <b>Chemical Resistance</b> | ASTM F925  | Good                                      |
| <b>Static Load Limit</b>   | ASTM F970  | Pass                                      |
| <b>Heat stability</b>      | ASTM F1514 | $\Delta E \leq 8.0$                       |
| <b>Slip resistance</b>     | ASTM D2047 | SCOF $\geq 0.6$                           |
| <b>Flammability</b>        | ASTM E648  | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Smoke Density</b>       | ASTM E662  | < 450                                     |
| <b>Hardness</b>            | ASTM D2240 | Not Less than 85 Shore A                  |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|                             | Standard | Tarkett value                       |
|-----------------------------|----------|-------------------------------------|
| <b>Cradle-to-Cradle</b>     | -        | Bronze                              |
| <b>ReStart®</b>             | -        | Yes                                 |
| <b>TVOC emission</b>        | -        | $\leq 500 \mu\text{g} / \text{m}^3$ |
| <b>Floorscore certified</b> | -        | Yes                                 |