



**BLOTTED
TEMPT Custom Collection
BL2X - 680
PRODUCT SPECIFICATIONS**

Style	Style: BL2X / Color: 680
Construction	Woven Axminster
Fiber	80% Wool / 20% Nylon
Dye Method	Yarn Dyed
Tufted Pile Weight	40 oz. Per Sq. Yard
Pile Height	.280 in.
Rows Per Inch	8
Pitch Per Inch	7
Primary Backing	Polypropylene
Secondary Backing	Copolymer
Total Thickness	.350 in.
Total Weight	56 oz.
Width	13 ft. 2 in.
Radiant Panel	Class 1
Smoke Density	Less than 450
Pattern Repeat	157.71 in W x 155.00 in L
Traffic Class	Heavy (Corridors/Public Space)

Recommended for heavy (corridor/public space) carpet traffic levels.

NOTE: Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.