



**MARIEKE X - MA010
PRODUCT SPECIFICATIONS**

Style	Marieke X - MA010
Construction	Digital Dye Injection
Fiber	100% Type 6 Nylon
Gauge	1/10
Tufted Pile Weight	36 oz. Per Sq. Yard
Pile Height	.250" Cut
Stitches Per Inch	12
Primary Backing	Woven Polypropylene
Secondary Backing	SB Latex Backing
Dye	Injection Dyed
Total Weight	72 oz.
Width	13 ft. 6 in.
Radiant Panel	Class 1
Smoke Density	Less than 450
Pattern Repeat	82.28 in. W x 109.72 in. L
Warranty	10 Year Wear Guarantee
Traffic Class	Heavy (Corridors/Public Space)

Recommended for heavy (corridors/public space) carpet traffic levels.

NOTE: Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.