



**SG620 Atlantis
PRODUCT SPECIFICATIONS**

Style	SG620 Atlantis
Construction	Dynamics – Servo-Scroll Loop Tip Shear
Fiber	100% C.F. Lextron Enviro Green Solution Dyed Nylon
Gauge	1/10
Tufted Pile Weight	32 oz. Per Sq. Yard
Pile Height	.250” High/ .187” Med./ .062” Low
Stitches Per Inch	10
Primary Backing	Woven Polypropylene
Secondary Backing	Action Bac
Dye	Solution Dyed
Total Weight	68 oz.
Width	12 ft.
Radiant Panel	Class 1
Smoke Density	Less than 450
Pattern Repeat	48 in. W x 48 in. L
Warranty	10 Year Wear Guarantee
Traffic Class	Moderate (Rooms)

Enviro-Green yarn has 10% pre-consumer recycled content.



Recommended for moderate (rooms) carpet traffic levels.

NOTE: Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute’s standard CRI-104. Carpet must be over manufacturer’s recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.