



## Savant #G0041

## Product Specification

Face Construction	Imperial		Metric	
Construction	Tufted Patterned Symtex®			
Face Weight	19	oz/sq yd	644.1	g/sq m
Gauge	1/10		39.4	rows/10 cm
Stitches per Inch	10.0		39.4	pu/10 cm
Tuft Density	100.0	tufts/sq in	15.5	tufts/sq cm
Pile Height Average	0.234	inch	5.9	mm
Pile Thickness	0.075	inch	1.9	mm
Density Factor	9,120	oz/cu yd	337.4	kg/cu m
Fiber System	Dynex SD® Nylon (Permanent Stain Resistance)			
Dye Method	Solution Dyed			
Fluorine-Free Soil Protection	Eco-Ensure		6.2	Kilotex
Primary Tufting Substrate	Synthetic Non-Woven			
Pattern Match	Not Required			

### Third Party Environmental Certifications

Product	Recycled Content*		NSF 140	Cradle to Cradle
	Overall	Postconsumer	SCS Certified	Certified™ v3.1**
Certified ethos® Modular with Omnicoat Technology™	47-75%	28%	Platinum	Silver

\*Minimum recycled content certified by Scientific Certification Systems (SCS) and varies by product style.

\*\*Cradle to Cradle Certified is a certification mark licensed by the Cradle to Cradle Products Innovation Institute

### Product Testing/Information

Antimicrobial Chemicals	No antimicrobials (EPA Registered pesticides) added to product (ASTM E2471-05)
Electrostatic Propensity	3.0 kV (AATCC 134); Permanent Conductive Fiber
Surface Flammability	Passes CPSC FF 1-70 (ASTM D-2859)
Flooring Radiant Panel	Class 1 (mean average CRF: 0.45 w/sq cm or higher) (ASTM E-648)
Smoke Generation	Less than 450 (ASTM E-662)
Colorfastness to Light	≥ 4 after 100 hours (AATCC 16E)
Soil Protection	Application Rate: 2% of Face Weight

### Installation Methods

Peel and Stick	RS Adhesive System - Full Coverage Peel & Stick
Wet Spread	Backing specific Tandus Adhesives
Installation Method	Vertical Ashlar; 18" x 36" and 9" x 36" Vertical Ashlar, Herringbone

### Product Notes

- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot.
- U.S. Patent numbers: 4,849,297; 4,849,267; 5,728,741; 5,855,981; 5,914,353; 6,406,574
- The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

### Tarkett North America

Technical Services Department  
 1000 Vista Drive  
 Dalton, GA 30721  
 800.248.2878 Fax 706.259.2136  
 info@tarkettna.com

[www.tarkettna.com](http://www.tarkettna.com)

© 2019 Tarkett USA Inc. 01/2019



## Modular Options

IMPERIAL

METRIC

TEST METHOD

**Warranty: Lifetime limited warranty against excessive surface wear, static, delamination, edge ravel, zippering & backing resiliency loss. Lifetime limited stain resistance.**

### ethos® Modular with Omnicoat Technology™

Total Minimum Recycled Content	57.5%		
Pre-Consumer	23.4%		
Postconsumer	34.1%		
Third Party Certification NSF-140	Platinum		
Cradle to Cradle Certification	Silver (Certification #1904)		
Product Size	24" x 24" Tile	(9" x 36" and 18" x 36" also available)	
Secondary Backing	50% Recycled Content		
Intermediate Layer	Fiberglass Reinforced Sealant		
Product Construction	No Delamination per ASTM D-3936		
Secondary Backing Density	65.0	lbs/cu ft	1041 kg/cu m
Secondary Backing Thickness	0.050	inch	1.3 mm
Total Weight	96.9	oz/sq yd +/-5%	3284.6 g/sq m
CRI Green Label Plus Certification	GLP8320		

SCS Certified total 47-75%  
 SCS Certified  
 SCS Certified  
 SCS Certified  
 Cradle to Cradle Certified™ v3.1

