

W0064 Fretwork

Collection	Iconic Threads Collection
Product Type	Broadloom
Style Number	W0064
Construction	Dynamics - Multi-Level Cut/Loop
Fiber	Lextron Enviro-Green Nylon 100
Dye Method	% Solution Dyed
Primary Backing	Woven Polypropylene
Secondary Backing	Action Bac

Size	12'
Gauge	1/10
Stitches per Inch	11
Tufted Weight	32 oz per sq/yd
Total Weight Density	66.2 oz
Finished Pile	3,767
Thickness Pattern	.278 inches
Repeat Overall	48 x 48
Thickness	.403 inches


Performance

Traffic Class (TARR)	Heavy
Pill Test	Pass
Radiant Panel	Class I
Flammability	ASTM E 648 Class I
Smoke Density	ASTM E 662 Less than 450
LEED Info	Green Label Plus Certified – GLP8320

Warranty	10 Year Limited Warranty
-----------------	---------------------------------

Available Customs

Backings	Unitary
Sizes	13' 6" and 15'

Enviro-Green yarn has 10% pre-consumer recycled content. 

Recommended for heavy (public space) carpet traffic levels.

NOTE: Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction.

IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.